

型号 Model			MS3.5-A3A	MS3.5-B3A	MS7-B3A	MS7-C3A	MS10-C3A
电源 Power supply		Ph-V-Hz	DC12V	DC24V	DC24V	DC48V	DC48V
制冷 Cooling	制冷量 Capacity	BTU	3,500	3,500	7,000	7,000	10,000
	额定功率 Input power	W	295	296	560	560	732
	额定电流 Rated current	A	26	13	26	26	15.2
	能效比 EER		3.5	3.5	3.8	3.8	4.0
制热 Heating	制热量 Capacity	BTU	4,000	4,000	7,500	7,500	11,500
	额定功率 Input power	W	310	310	540	540	785
	额定电流 Rated current	A	27	13.5	25	25	16.3
	性能系数 COP		3.8	3.8	4.0	4.0	4.3
最大运行电流 Max. current		A	31	16	28	28	19.5
海水流量 Sea water flow		m³/h	0.35	0.45	0.46	0.46	0.51
风量 Indoor air flow		m³/h	250	250	290	290	480
除湿量 Dehumidification capacity		L/h	0.6	0.6	0.7	0.7	1.5
噪音 Noise level		dB(A)	≤55	≤55	≤55	≤55	≤51
产品尺寸(L×W×H) Dimension (L*W*H)		mm	490×236×282		484×236×318		598×365×346
电控盒尺寸 Control box (L*W*H)		mm	432×186×92				
净重 Net weight		Kg	20	20	25	25	31
冷媒种类 Refrigerant type			R134a				
出风口尺寸 Fan duct size		mm	Φ100	Φ100	Φ100	Φ100	Φ150
海水接口 Sea water pipe		mm	G1/2"-16				
冷凝水接口 Condensed water pipe		mm	G1/2"-19				

